



Printing date 12.08.2015

Revision: 20.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

For professional use only

· 1.1 Product identifier For professional use only

- Trade name: Craftmaster PPA Brushing Additive
- · Article number: 5651
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Surface Coating
- · Application of the substance / the mixture Surface Coating Surface Coating
- · 1.3 Details of the supplier of the safety data sheet
- Supplier: **Craftmaster Paint Ltd Acadamy Works** Norman Way Ind Est Over Cambs **CB24 5OE**
- · Further information obtainable from: Craftmaster
- · 1.4 Emergency telephone number: 01954 231 308

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Asp. Tox. 1

GHS08 health hazard

H304 May be fatal if swallowed and enters airways.

GHS09 environment

H400 Very toxic to aquatic life. Aquatic Acute 1 Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

GHS07

H315 Causes skin irritation. Skin Irrit, 2 Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Printing date 12.08.2015

Revision: 20.05.2015

(Contd. of page 1)

Trade name: Craftmaster PPA Brushing Additive

• Hazard pictograms GHS02, GHS07, GHS08, GHS09 • Signal word Danger

Hazard-determining components of labelling:

p-mentha-1,8(9)-diene Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 2-butanone oxime cobalt bis(2-ethylhexanoate)

Hazard statements

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Very toxic to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. • 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|------------------------------------|---|---------------|
| CAS: 138-86-3 EINECS: 205-341-0 | p-mentha-1,8(9)-diene Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317 | 50-100% |
| EC number: 919-857-5 | Hydrocarbons, C9 - C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; SAsp. Tox. 1, H304; STOT SE 3, H336 | 10-25% |
| EC number: 919-446-0 | Hydrocarbons C9-12 N-Alkanes, Isoakanes Cyclic Aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 | <u>≤</u> 2.5% |
| CAS: 96-29-7 EINECS: 202-496-6 | 2-butanone oxime | ≤ 2.5% |
| CAS: 136-52-7 EINECS: 205-250-6 | cobalt bis(2-ethylhexanoate) Repr. 2, H361; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | ≤ 2.5% |

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation:

Supply fresh air and call for a doctor.

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

Printing date 12.08.2015

Trade name: Craftmaster PPA Brushing Additive

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water Water with full jet

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

. 5.3 Advice for firefighters

· Protective equipment: Put on breathing apparatus

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or acueous cleansing agents

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Prevent formation of aerosols.

Hygiene measures:

Wash hands before breaks and at the end of workday.

Use protective skin cream before handling the product.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect from heat.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed and in a well-ventilated place. Keep away from heat.

Printing date 12.08.2015

Revision: 20.05.2015

Trade name: Craftmaster PPA Brushing Additive

(Contd. of page 3)

Protect from heat and direct sunlight. • 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eves and skin.

· Respiratory protection:

When spraying the product, use a respiratory protective device. If spraying this product, an ABEK respirator to EN141 and EN405 is normally suficient. If in doubt, consult a respirator manufacturer and show this safety data sheet.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- General Information Appearance: Form: Colour: Odour:
- Liquid Clear Characteristic

Printing date 12.08.2015

Revision: 20.05.2015

Trade name: Craftmaster PPA Brushing Additive

(Contd. of page 4)

| Odour threshold: | Not determined. |
|---|---|
| pH-value: | Not determined. |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | Undetermined. 150 °C |
| Flash point: | 40 °C |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | 255 °C |
| Decomposition temperature: | Not determined. |
| Self-igniting: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapou mixtures are possible. |
| Explosion limits: Lower: Upper: | 0.7 Vol % 6.1 Vol % |
| Vapour pressure at 20 °C: | 2.1 hPa |
| Density at 20 °C: Relative density Vapour density Evaporation rate | 0.894 g/cm ³ Not determined. Not determined. Not determined. |
| Solubility in / Miscibility with water: | NOT MISCIBLE |
| Partition coefficient (n-octanol/wat | ter): Not determined. |
| Viscosity: Dynamic: Kinematic at 20 °C: | Not determined. 13 s (DIN 53211/4) |
| Solvent content: Organic solvents: | 60.3 % |
| Solids content: 9.2 Other information | 27.5 % No further relevant information available. |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

No dangerous decomposition products when stored and handled correctly

Printing date 12.08.2015

Revision: 20.05.2015

Trade name: Craftmaster PPA Brushing Additive

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >3000 mg/kg (rab)

- Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Trade name: Craftmaster PPA Brushing Additive

| SECTION 14: Transport informat | |
|---|--|
| 14.1 UN-Number ADR, IMDG, IATA | UN1263 |
| 14.2 UN proper shipping name ADR | 1263 PAINT RELATED MATERIAL (not viscou ENVIRONMENTALLY HAZARDOUS |
| IMDG | PAINT RELATED MATERIAL (DIPENTEN TURPENTINE SUBSTITUTE), MARINE POLLUTANT |
| IATA | PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es) | |
| ADR, IMDG | |
| Class Label | 3 Flammable liquids. 3 |
| | |
| Class Label | 3 Flammable liquids. 3 |
| 14.4 Packing group ADR, IMDG, IATA | 111 |
| 14.5 Environmental hazards: | Product contains environmentally hazardous substanc p-mentha-1,8(9)-diene |
| Marine pollutant: | Symbol (fish and tree) Symbol (fish and tree) |
| Special marking (ADR): 14.6 Special precautions for user | Warning: Flammable liquids. |
| Danger code (Kemler): EMS Number: | 30 F-E,S-E |
| 14.7 Transport in bulk according to Anno Marpol and the IBC Code | |
| Transport/Additional information: | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport category Tunnel restriction code | 3 D/E |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |

Printing date 12.08.2015

Revision: 20.05.2015

(Contd. of page 7)

Trade name: Craftmaster PPA Brushing Additive

UN1263, PAINT RELATED MATERIAL (not viscous). UN "Model Regulation": ENVIRONMENTALLY HAZARDOUS, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| Ι | 0.2 |
| NK | 60.3 |

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

H226 Flammable liquid and vapour.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. Department issuing MSDS: Product safety department: LABORATORY · Contact: Health & Safety Officer · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3

Printing date 12.08.2015

Trade name: Craftmaster PPA Brushing Additive

Revision: 20.05.2015

(Contd. of page 8)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3