

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier** For professional use only
- **Trade name:** Craftmaster Anti Corrosive Grey Primer
- **Article number:** 7119
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture** Surface Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:** Craftmaster Paints Ltd  
Academy Works  
Norman Way Ind Est  
Over, Cambs, CB24 5QE  
info@craftmasterpaints.co.uk
- **Further information obtainable from:**
- **1.4 Emergency telephone number:** 01954 231 308

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 1      H372 Causes damage to organs through prolonged or repeated exposure.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS02, GHS08, GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Naphtha (petroleum), hydrosulphurized heavy; low boiling point treated naphtha  
Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)
- **Hazard statements**  
Flammable liquid and vapour.  
Causes damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

**Trade name:** Craftmaster Anti Corrosive Grey Primer

(Contd. of page 1)

**Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains p-mentha-1,8(9)-diene, 2-butanone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

**2.3 Other hazards****Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

EC number: 919-446-0	Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-50%
CAS: 7779-90-0 EINECS: 231-944-3	zinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-10%
CAS: 138-86-3 EINECS: 205-341-0	p-mentha-1,8(9)-diene Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	≤ 2.5%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime Carc. 2, H351; Eye Dam. 1, H318; Acute Tox. 4, H312; Skin Sens. 1, H317	≤ 2.5%
CAS: 136-52-7 EINECS: 205-250-6	cobalt bis(2-ethylhexanoate) Repr. 2, H361; Aquatic Acute 1, H400; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≤ 2.5%

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:**

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:**

Water

(Contd. on page 3)

## **Safety data sheet**

### **according to 1907/2006/EC, Article 31**

Printing date 28.07.2015

Revision: 12.05.2015

**Trade name:** Craftmaster Anti Corrosive Grey Primer

(Contd. of page 2)

*Water with full jet*

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
*Wear protective equipment. Keep unprotected persons away.*
- **6.2 Environmental precautions:**  
*Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.*

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
*Keep receptacles tightly sealed.  
Ensure good ventilation/extraction at the workplace.  
Prevent formation of aerosols.  
Hygiene measures:  
Wash hands before breaks and at the end of workday.  
Use protective skin cream before handling the product.*
- **Information about fire - and explosion protection:**  
*Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
*Keep receptacle tightly sealed and in a well-ventilated place.  
Keep away from heat.  
Protect from heat and direct sunlight.*
- **7.3 Specific end use(s)** No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
*The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

**Trade name:** Craftmaster Anti Corrosive Grey Primer

(Contd. of page 3)

· <b>DNELs</b>		
<b><i>Naphtha (petroleum), hydrosulphurized heavy; low boiling point treated naphtha</i></b>		
Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
		44 mg/day (Ind)
Inhalative	DNEL	71 mg/m <sup>3</sup> (Con)
		330 mg/m <sup>3</sup> (Int)
<b><i>Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)</i></b>		
Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	26 mg/day (Con)
		44 mg/day (Ind)
Inhalative	DNEL	71 mg/m <sup>3</sup> (Con)
		330 mg/m <sup>3</sup> (Int)

· **PNECs**

CAS No. 1330-20-7 Xylene mixed isomers

- Fresh water; 0.327 mg/l
- Marine water; 0.327 mg/l
- Intermittent release; 0.327 mg/l
- STP; 6.58 mg/l
- Sediment (Freshwater); 12.46 mg/kg
- Sediment (Marinewater); 12.46 mg/kg
- Soil; 2.31 mg/kg

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.

· **Respiratory protection:** When spraying the product, use a respiratory protective device.· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

Trade name: Craftmaster Anti Corrosive Grey Primer

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

· <b>9.1 Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
Form:	Liquid
Colour:	Dark grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· <b>Change in condition</b>	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	135 °C
· Flash point:	31 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.343 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	NOT MISCIBLE
· Partition coefficient (n-octanol/water):	Not determined.
· <b>Viscosity:</b>	
Dynamic at 20 °C:	140 mPas
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	1.7 %
Solids content:	67.3 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

Trade name: Craftmaster Anti Corrosive Grey Primer

(Contd. of page 5)

- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

#### Naphtha (petroleum), hydrosulphurized heavy; low boiling point treated naphtha

Oral	LD50	>5050 mg/kg (Rat)
Dermal	LD50	>4 mg/kg (Rab)
Inhalative	LC50/4 h	>13.1 mg/l (Rat)

#### Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)

Oral	LD50	>15000 mg/kg (Rat)
Dermal	LD50	>3400 mg/kg (Rab)
Inhalative	LC50/4 h	13.1 mg/l (Rat)

#### 7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**  
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

Trade name: Craftmaster Anti Corrosive Grey Primer

(Contd. of page 6)

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**

· **ADR**

1263 PAINT (not viscous), ENVIRONMENTALLY HAZARDOUS

· **IMDG**

PAINT (TURPENTINE SUBSTITUTE, trizinc bis(orthophosphate)), MARINE POLLUTANT

· **IATA**

PAINT

· **14.3 Transport hazard class(es)**

· **ADR, IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: trizinc bis(orthophosphate), Hydrocarbons C9-12 N-Alkanes, Isoalkanes Cyclic Aromatics (2-25%)

· **Marine pollutant:**

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):**

30

· **EMS Number:**

F-E,S-E

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.07.2015

Revision: 12.05.2015

Trade name: Craftmaster Anti Corrosive Grey Primer

(Contd. of page 7)

· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	500 ml
· <b>Excepted quantities (EQ)</b>	Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· <b>UN "Model Regulation":</b>	UN1263, PAINT (not viscous), ENVIRONMENTALLY HAZARDOUS, 3, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
I	0.3
NK	1.7

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· **Department issuing MSDS:** Product safety department: LABORATORY

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 28.07.2015

Revision: 12.05.2015

**Trade name: Craftmaster Anti Corrosive Grey Primer**

(Contd. of page 8)

*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*DNEL: Derived No-Effect Level (REACH)*  
*PNEC: Predicted No-Effect Concentration (REACH)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*Flam. Liq. 3: Flammable liquids, Hazard Category 3*  
*Acute Tox. 4: Acute toxicity, Hazard Category 4*  
*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*  
*Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1*  
*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*  
*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*  
*Carc. 2: Carcinogenicity, Hazard Category 2*  
*Repr. 2: Reproductive toxicity, Hazard Category 2*  
*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*  
*STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1*  
*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*  
*Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*  
*Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3*

GB