

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Repair Stick Multi-Purpose
Code-Nr. 105390

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

2-Component Epoxy Resins

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone +49(0)251 / 9322 - 0
Fax +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster,

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 3	H412	

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS07

Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

2-component epoxy sticks

**Repair Stick Multi-Purpose****! Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1 < 5	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	10 < 20	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
65997-17-3	266-046-0	glass, oxide, chemicals	10 - 20	
72244-98-5	615-735-8	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	10 < 20	Skin Sens. 1B, H317 / Aquatic Chronic 3, H412

REACH

CAS No	Name	REACH registration number
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	01-2119560597-27
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
72244-98-5	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	01-2120118957-46

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

skin irritation

Physician's information / possible dangers

allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam
Dry fire-extinguishing substance
Carbon dioxide
Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO_x)
Carbon monoxide (CO)
Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Remove persons to safety.
Use personal protective clothing.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into surface waters/groundwater.
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

After taking up the material dispose according to regulation.
Take up mechanically.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.
Avoid contact with eyes and skin

**Repair Stick Multi-Purpose****Hygiene measures**

At work do not eat, drink, smoke or take drugs.
Remove soiled or soaked clothing immediately.
Work in rooms with good ventilation.
Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.
Do not store together with food.
Do not store together with acids.
Do not store together with oxidizing agents.

Further information on storage conditions

Protect from heat and direct solar radiation.
Store container at cool and aired place.
Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005
14807-96-6	Talk astbestfaserfrei (CH)	MAK, 8 hours	2		Lungenfib, Lunge, Methode: OSHA

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		12,25 mg/m ³	DNEL long-term inhalative (systemic)	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,31 mg/m ³	DNEL long-term inhalative (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	10 mg/l	PNEC sewage treatment plant (STP)	

**Repair Stick Multi-Purpose****DNEL-/PNEC-values (continued)**

CAS No	Substance name	Value	Code	Remark
		11 mg/kg	PNEC Secondary Poisoning	
		0,0996 mg/kg	PNEC sediment, marine water	
		0,996 mg/kg	PNEC sediment, freshwater	
		0,018 mg/l	PNEC aquatic, intermittent release	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0006 mg/l	PNEC aquatic, marine water	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,2 mg/l	PNEC sewage treatment plant (STP)	
		0,084 mg/l	PNEC aquatic, freshwater	
		0,0084 mg/l	PNEC aquatic, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

solid mass

Colour

white

Odour

sulphur-like

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	> 35 °C		ca. 1,01 bar		
melting point	not applicable				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 27.02.2019

revision 23.01.2019 (GB) Version 1.1

Repair Stick Multi-Purpose

	Value	Temperature	at	Method	Remark
Flash point	> 100 °C				
Vapourisation rate	not applicable				
Flammable (solid)	not determined				
Flammability (gas)	not applicable				
Ignition temperature	not determined				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 500 Pa	20 °C			
Relative density	ca. 1,95 g/cm ³				
Vapour density	not applicable				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	not applicable				
Viscosity kinematic	not applicable				
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidising agents.

Reactions with amines.

**10.4. Conditions to avoid**

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Amines

Acid

Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NO_x)

Toxic gases/vapours

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	20833 mg/kg			ATE
LD50 acute dermal	1200 mg/kg	rat		CAS: 25068-38-6
Skin irritation	irritant			
Eye irritation	irritant			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity				-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Sensitization through skin contact possible.

Irritates mucous membranes.

Irritates eyes and skin.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

! SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 2 mg/l (96 h)	Oncorhynchus mykiss		CAS: 25068-38-6
Daphnia	EC50 1,8 mg/l (48 h)	Daphnia magna		CAS: 25068-38-6
Algae	EC50 220 mg/l (96 h)	Scenedesmus subspicatus		CAS: 25068-38-6

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	12 % (28 d) CAS: 25068-38-6			not degradable

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

08 04 09*

15 01 10*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Uncontaminated packaging may be treated as household waste.

Packaging that cannot be cleaned should be disposed of like the product.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Transport/further information	No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.0

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 27.02.2019

revision 23.01.2019 (GB) Version 1.1

Repair Stick Multi-Purpose

H412 Harmful to aquatic life with long lasting effects.